

AU6-25/35L



Sensor Resolution (pixel)	640×512
Sensor Pixel Size	12μm
Objective Lens (mm)	25/35mm
Frame Rate (HZ)	50HZ
Field-of-View	17.5°×14°/12.5°×10°
Optical Magnification (x)	1.4/2.0
Digital Zoom (x)	1x,2x,4x,8x
Display Type/Resolution)	1024×768
Color Mode	White Hot, High Contrast, Black Hot, Low Light, Fusion
Reticle Design Options	10
Reticle Color Options	3
Multiple Gun Profiles	10
Detection Range	>2500m/>3500m
Recognition and Identification Range	900/1300
Laser Rangefinder Range	1000m
NETD	≤18mk
Start-Up Time/Cold Start	7s
Start-Up Time/Power Saver Mode	7s
On-board video recording	Yes
Video Output	/
WIFI Equipped	Yes
Battery Type	18650
Expected Battery Runtime	≥5H
External Power Supply Capable	Yes
Recoil Resistance (G)	/
Operating Temperature	-20°C~+50°C
Dimensions	176×48.4×82.9mm
Weight (w/o Mount & Battery)	384g
Waterproof Rating	IP67

ACCESSORY



Zippered Bag



Product Manual



Charger Plug



Type-C Data Cable



18650 Battery