

MN2-19/25L



Sensor Resolution (pixel)	256×192
Sensor Pixel Size	12μm
Objective Lens (mm)	19/25mm
Frame Rate (HZ)	50HZ
Field-of-View	9.2°×6.9°/7°×5.3°
Optical Magnification (x)	2.8/3.6
Digital Zoom (x)	1x,2x,4x,8x
Display Type/Resolution	1024×768
Color Mode	White Hot, High Contrast, Black Hot, Low Light, Fusion
Reticle Design Options	10
Reticle Color Options	3
Multiple Gun Profiles	10
Detection Range	>2500m/>3500m
Recognition and Identification Range	700/900
Laser Rangefinder Range	1000m
NETD	≤25mk
Start-Up Time/Cold Start	7s
Start-Up Time/Power Saver Mode	7s
On-board video recording	Yes
Video Output	/
WIFI Equipped	Yes
Battery Type	18650
Expected Battery Runtime	≥5H
External Power Supply Capable	Yes
Recoil Resistance (G)	1000G
Operating Temperature	-20°C~+50°C
Dimensions	185.3×83.2×56.3mm
Weight (w/o Mount & Battery)	478g
Waterproof Rating	IP67

ACCESSORY



Zippered Bag



Product Manual



Picatinny mount



Installation tool accessories



Charger Plug



Type-C Data Cable



18650 Battery